

UNIVERSAL ROAD MASTER

Road Marking Traffic Paint



DESCRIPTION:

A fast drying alkyd-type road marking and traffic paint specifically developed to perform well on highways, roadways, airfields and parking lots.

This product dries to an extremely durable, skid- and fade- resistant and hard wearing film available in reflectorized & non-reflectorized variants

RECOMMENDED USES:

Extreme road environment conditions such as highways, roadways, airfields, and parking lots.

PRODUCT APPEARANCE	: Liquid
PACKAGE VISCOSITY	: 80-85 kus
DRY FILM THICKNESS	:
DRY SET TO TOUCH	: 1 hour
DRY HARD	: 8 hours
COATING INTERVAL	: 4 hours
THINNING	: Traffic Paint Reducer
APPLICATION	: brush, roller
COVERAGE	: 20-25 m ² /4L depending on surface porosity & texture
CLEAN-UP	: Traffic Paint Reducer
PACKAGING SIZE	: 4 liters
AVAILABLE COLORS	: White PRO-650, Yellow PRO-651, Black PRO-652

SURFACE PREPARATION:

Masonry

New or unpainted surface

Remove dirt, dust, grit, loose mortar, oil, grease and other contaminants. New concrete must be cured at least 28 days before paint application. Please follow manufacturer's recommendation to check use litmus paper test.

Old or previously painted surface

Remove all loose, peeling, chalking or blistering paint, dirt, dust, grease, oil and other contaminants. Treat mold or fungus infestation with bleaching solution (1 part bleach and 3 parts water).

Metal

New or unpainted surface

Ensure that the metal surface is free from oil, grease, rust, and other surface contaminants. Remove thick rust by sand blasting and thin rust by wire brushing, sanding or scraping. Dust the surface and wipe surface clean prior to priming with metal primer red oxide.

Old or previously painted surface

Remove all loose, peeling, paint, rust, dirt, dust, grease, oil and other contaminants by wire brushing or scraping. Wipe surface clean and priming with metal primer red oxide.

APPLICATION:

Do not thin. Inter-mix all cans of same color to ensure color uniformity and consistency. Always stir paint before and occasionally during application. Apply only when temperature is from 10° – 35°C. Do not paint in rain or rain imminent weather. For best results always use high quality roller and brush.

UNIVERSAL ROAD MASTER

Road Marking Traffic Paint



PAINTING DIRECTIONS: For best results use:

- 1st coat: Universal Road Master ReflectORIZED Traffic Paint PRO-XXX,
Allow 4 hours drying time.
- 2nd coat: Universal Road Master ReflectORIZED Traffic Paint of desired reflectance & color
Allow 8 hours drying time.

Apply more coats if higher hiding is desired.