

UNIVERSAL FLOOR MASTER

Epoxy Floor Coating Topcoat



DESCRIPTION:

A premium quality industrial grade topcoat for Universal Floor Master Epoxy Floor Coating System.

This product is high build topcoat formulated for heavy-duty floor protection. It features excellent surface adhesion, chemical and solvent resistance, and exceptional abrasion resistance, thus requiring less surface maintenance. This system is classified as a) Light b) Medium, or c) Heavy grade protection.

RECOMMENDED USES:

Interior concrete surfaces.

PRODUCT APPEARANCE	: Liquid
PACKAGE VISCOSITY	: 65-70 kus
INDUCTION TIME	: 15 minutes
DRY FILM THICKNESS	:
DRY SET TO TOUCH	: 4 hours
DRY HARD	: 48 hours pedestrian traffic
COATING INTERVAL	: 24 hours
THINNING	: Epoxy Reducer
APPLICATION	: brush, roller, spray
COVERAGE	: 20-25 m ² /4L depending on surface porosity & texture
CLEAN-UP	: Epoxy Reducer
PACKAGING SIZE	: 4 liters
AVAILABLE COLORS	: Clear PRO-750 Black PRO-752 Winter White PRO-751 Battleship Gray PRO-754 Smoke Gray PRO-754A Pine Green PRO-755 Safety Yellow PRO-756 Cardinal Red PRO-757 Safety Orange PRO-758 Riviera PRO-761 Blue Bay PRO-753 Ocean Blue PRO-753A Granite PRO-762 Onyx PRO-763 Pale Pewter PRO-759 Dune Beige PRO-760
MIXING RATIO	: 3parts Universal Floor Master Floor Coating Topcoat PRO-XXX 1 part FC catalyst <i>Color can be customized. Please call us for details.</i>
FINISH	: Gloss

SURFACE PREPARATION:

New or unpainted surface

Remove dirt, dust, grit, loose mortar, oil, grease and other contaminants. New concrete must be cured at least 28 days before paint application. Please follow manufacturer's recommendation to check use litmus paper test.

Old or previously painted surface

Remove all loose, peeling, chalking or blistering paint, dirt, dust, grease, oil and other contaminants. Treat mold or fungus infestation with bleaching solution (1 part bleach and 3 parts water).

UNIVERSAL FLOOR MASTER

Epoxy Floor Coating Topcoat



APPLICATION:

Do not thin. Inter-mix all cans of same color to ensure color uniformity and consistency. Always stir paint before and occasionally during application. Apply only when temperature is from 10° – 35°C. Do not paint in rain or rain imminent weather. For best results always use high quality roller and brush.

PAINTING DIRECTIONS: For best results use:

- 1st coat: Universal Floor Master Deep Penetrating Sealer PRO-730.
Allow 4 hours drying time.
- 2nd coat: Universal Floor Master Epoxy Floor Primer PRO-XXX.
Allow 4 hours drying time then sand lightly.

To remedy surface imperfections:

Repair with Polyester Polybond Bodyfiller. Allow 4 hours drying time.

Spot prime with Universal Floor Master Epoxy Floor Primer PRO-XXX. Allow 4 hours drying time.

- 3rd – 4th coat: Universal Floor Master Epoxy Floor Topcoat of desired color.
Allow 24 hours drying time between coats.

Apply more coats if higher hiding is desired.