

# UNIVERSAL AQUAGUARD

## Elastomeric Paint



### DESCRIPTION:

The AquaGuard Elastomeric Paint is a premium quality, high build elastomeric coating that *dries* to a *satin* or *semi-gloss* finish

This product provides long-lasting protection against extreme heat or rainy conditions. Unlike typical exterior paints, AquaGuard forms a tough and flexible barrier which bridges hairline cracks and pinholes. It seals exterior surfaces against water intrusion from light to typhoon level wind-driven rain and at the same time resists paint blistering by allowing trapped moisture to escape.

### RECOMMENDED USES:

Interior and exterior masonry walls and ceilings, concrete hollow blocks, masonry constructions, and properly primed galvanized iron roofing.

PRODUCT APPEARANCE	: Liquid
PACKAGE VISCOSITY	: 105-115 kus
DRY FILM THICKNESS	:
DRY SET TO TOUCH	: 30 minutes
DRY HARD	: 2 hours
COATING INTERVAL	: 1-2 hours
THINNING	: Apply at package consistency
APPLICATION	: brush, roller
COVERAGE	: 25-30 m <sup>2</sup> /4L depending on surface porosity & texture
CLEAN-UP	: Water
PACKAGING SIZE	: 1, 4, 16 liters
AVAILABLE COLORS	: 1000's of colors with Universal Color Depot <i>Custom colors available. Call us for details.</i> Maybe tinted using Universal Acri-color

### SURFACE PREPARATION:

#### New or unpainted surface

Remove dirt, dust, grit, loose mortar, oil, grease and other contaminants. New concrete must be cured at least 28 days before paint application. Please follow manufacturer's recommendation to check use litmus paper test.

#### Old or previously painted surface

Remove all loose, peeling, chalking or blistering paint, dirt, dust, grease, oil and other contaminants. Treat mold or fungus infestation with bleaching solution (1 part bleach and 3 parts water).

### APPLICATION:

Do not thin. Inter-mix all cans of same color to ensure color uniformity and consistency. Always stir paint before and occasionally during application. Apply only when temperature is from 10° – 35°C. Do not paint in rain or rain imminent weather. For best results always use high quality roller and brush.

**PAINTING DIRECTIONS:** For best results use:

# UNIVERSAL AQUAGUARD

## Elastomeric Paint



New concrete:

1<sup>st</sup> coat: AquaGuard Satin Finish White AG-100. Allow 1-2 hours drying time.

**To remedy surface imperfections:**

Putty: AquaPutty AGS-600. Allow 4 hours drying time.

Spot Prime: Aquaguard Satin Finish White AG-100

2<sup>nd</sup>-3<sup>rd</sup> coat AquaGuard Premium Elastomeric of desired sheen & color.

Old concrete:

1<sup>st</sup> coat: Aqua Guard Satin Finish White AG-100.

**To remedy surface imperfections:**

Putty: AquaPutty AGS-600

Spot Prime: Aquaguard Satin Finish White AG-100.  
Allow 1-2 hours drying time between coats.

2<sup>nd</sup>-3<sup>rd</sup> coat AquaGuard Premium Elastomeric of desired sheen & color.

For texture finish: See Universal AquaShield Cementitious Elastomeric Coating

Apply more coats if higher hiding or thickness is desired.